

MasterRoc[®] MS 610

(Formerly known as MEYCO MS 610)

Densified silica fume for cast and sprayed concrete

DESCRIPTION

MasterRoc MS 610 is a high quality silica fume powder for high performance concretes. It changes the porous structure of the concrete making it denser and more resistant to any type of external influence.

FIELDS OF APPLICATION

- Wet-mix sprayed concrete applications
- Pre-cast concrete
- Cast in-situ concrete
- High strength concrete
- Underwater concrete
- Concrete with low cement content
- Annulus grouting (TBM)

FEATURES AND BENEFITS

- Wet-mix sprayed concrete applications
- Pre-cast concrete
- Cast in-situ concrete
- High strength concrete
- Underwater concrete
- Concrete with low cement content
- Annulus grouting (TBM)

PACKAGING

MasterRoc MS 610 is supplied in 20 kg plastic bags and big bags.

TECHNICAL DATA*

Form	Powder
Color	Grey
Density	0.55 - 0.7 kg/l
Chloride content	<0.1%

COMBINATION

The use of superplasticizers is recommended for any silica fume concrete. For frost resistance, an additional air-entraining agent must be added.

MIXING

MasterRoc MS 610 is added to the concrete during batching. Minimum mixing time is 90 seconds. The recommended dosage is 5 to 15% of the cement weight.

STORAGE

If stored dry and in tightly closed original bags, **MasterRoc MS 610** has a shelf life of at least 12 months.



We create chemistry

MasterRoc[®] MS 610

(Formerly known as MEYCO MS 610)

SAFETY PRECAUTIONS

Avoid contact with eyes and prolonged contact with skin. If contact occurs, wash thoroughly with water and seek medical advice.

For further information refer to the product Material Safety Data Sheet.

* Properties listed are based on laboratory controlled tests.

® = Registered trademark of the BASF-Group in many countries.

BASF_CC-UAE/Roc_MS610/v1/10_13

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this BASF publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by BASF either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not BASF, are responsible for carrying out procedures appropriate to a specific application.

BASF Construction Chemicals UAE LLC

P.O. Box 37127, Dubai, UAE

Tel: +971 4 8090800

Fax: +971 4 8851002

www.master-builders-solutions.basf.ae

